1   **What is claimed is:**

2   1.   A method of defining a storage format in multiple data storage

3   devices, each data storage device having a plurality of storage media and a

4   plurality of corresponding data transducer heads, each transducer head for

5   recording on and playback of information from a corresponding storage medium

6   in multiple zones, the method comprising the steps of:

7   (a)   (1) for a sample number of data storage devices, measuring a

8   performance of each head in the sample number of data storage devices at one

9   or more read/write frequencies per zone, and

10   (2) for said multiple data storage devices, based on said

11   performance measurements, jointly: selecting a group of read/write frequencies,

12   two or more read/write frequencies for each zone, and allocating one or more of

13   the heads in each of the multiple data storage devices to each frequency in said

14   group of frequencies per zone; and

15   (b)   in each of said multiple data storage devices, assigning one of said

16   frequencies to each head per zone, based on capability of that head.

17

18   2.   The method of claim 1, wherein in step (a)(1) measuring

19   performance of each head further includes the steps of measuring a

20   record/playback performance of that head at one or more read/write frequencies.

21

22   3.   The method of claim 1, wherein in step (a)(1) measuring

23   performance of each head further includes the steps of measuring a

24   record/playback performance of that head at multiple storage medium locations.

25

26   4.   The method of claim 1, wherein in step (a)(1) measuring

27   performance of each head further includes the steps of measuring a

28   record/playback performance of that head according to a performance metric at

29   different frequencies.

30

1   5.   The method of claim 4, wherein said performance metric includes

2   symbol error rate on track, symbol error rate off track, mean squared error on

3   track, and mean squared error off track.

4

5   6.   The method of claim 1, wherein step (a) is performed in a format

6   design process and step (b) is performed in a test process.

7

8   7.   The method of claim 6, wherein the format design process is part of

9   storage device design phase and the test process is part of storage device

10   manufacturing phase.

11

12   8.   The method of claim 1, wherein step (a)(1) further includes the

13   steps of calibrating each of said multiple data storage devices for each said

14   frequencies.

15

16   9.   The method of claim 1, wherein step (a)(2) further includes the

17   steps of jointly selecting said frequencies and allocating said heads to said

18   frequencies, to satisfy a specified constraint.

19

20   10.   The method of claim 9, wherein:

21   step (a)(1) further includes the steps of, for each of said sample

22   number of data storage devices:

23   selecting a performance metric for the heads in that data

24   storage device for each zone; and

25   measuring performance of each head at different

26   frequencies per zone based on said metric;

27   step (a)(2) further includes the steps of, for the multiple data

28   storage devices:

29   based on said performance measurements, for each zone

30   allocating an integral number of heads to each of said frequencies for that zone

31   to satisfy

1 the specified constraint.

2

3   11.   The method of claim 10, wherein in step (a)(2) allocating said

4 heads to said frequencies per zone further includes the steps of: for each zone,

5 based on the performance of the heads in a plurality of zones, allocating an

6 integral number of heads to each of said frequencies for that zone to satisfy said

7 constraint for said multiple data storage devices.

8

9   12.   The method of claim 10, wherein step (a)(2) further includes the

10 steps of:

11   based on said performance measurements, generating

12 record/playback frequency capability distributions of the heads in the sample

13 number of disk drives, at each zone for a target performance metric, and

14   based on said distributions, allocating an integral number of heads

15 to each of said frequencies for that zone to satisfy said constraint for the said

16 multiple data storage devices.

17

18   13.   The method of claim 9, wherein said constraint comprises providing

19 a required data storage capacity for each of said multiple data storage devices.

20

21   14.   The method of claim 9, said constraint comprises providing a

22 required data storage device yield for said multiple data storage devices.

23

24   15.   The method of claim 9, wherein said constraint comprises

25 maximizing the data storage device yield while providing a specified data storage

26 device capacity of the multiple data storage devices.

27

28   16.   The method of claim 9, wherein said constraint comprises

29 maximizing the data storage capacity for each of the multiple data storage

30 devices while providing a specified data storage device yield.

31

17.   A method of defining a storage format in multiple data storage devices, each data storage device having a plurality of storage media and a plurality of corresponding data transducer heads, each transducer head for recording on and playback of information from a corresponding storage medium in multiple zones, the method comprising the steps of:

    (a)   (1) for a sample number of data storage devices, measuring a performance of each head in the sample number of data storage devices at one or more read/write frequencies per zone, and based on said performance measurements, generating performance distributions of the heads in said sample number of data storage devices, at each zone for a target performance metric, and

        (2) for said multiple data storage devices, based on said performance distributions, jointly: selecting a group of read/write frequencies, two or more read/write frequencies for each zone, and allocating one or more of the heads in each of the multiple data storage devices to each frequency in said group of frequencies per zone; and

    (b)   in each of said multiple data storage devices, assigning one of said frequencies to each head per zone, based on capability of that head.

18.   The method of claim 17, wherein generating said distributions further includes the steps of:

        estimating record/playback frequency capability of each head based on said measurements, and

        generating record/playback frequency capability distributions of the heads at each zone for a target performance metric based on said estimated record/playback frequency capabilities the heads.

19.   The method of claim 17, wherein the steps of generating said distributions is performed in a post-processing phase.

52

1   20. The method of claim 17, wherein generating said distributions

2 includes the steps of: generating record/playback frequency capability

3 distributions of the heads based on said performance measurements at a target

4 performance metric for the heads in said sample number of data storage devices.

5

6   21. The method of claim 17, wherein in step (a)(2) selecting said group

7 of frequencies further includes the steps of selecting said group of frequencies to

8 satisfy a specified constraint.

9

10   22. The method of claim 17, wherein said performance metric includes

11 symbol error rate on track, symbol error rate off track, mean squared error on

12 track, and mean squared error off track.

13

14   23. A method of defining a storage format in multiple data storage

15 devices, each data storage device having a plurality of storage media and a

16 plurality of corresponding data transducer heads, each transducer head for

17 recording on and playback of information from a corresponding storage medium

18 in multiple zones, the method comprising the steps of:

19   (a) (1) for a sample number of data storage devices, measuring a

20 performance of each head in the sample number of data storage devices at one

21 or more read/write frequencies per zone, and

22   (2) for said multiple data storage devices, based on said

23 performance measurements, jointly: selecting a group of read/write frequencies,

24 two or more read/write frequencies for each zone, and for each zone allocating

25 an integral number of heads to each of said frequencies for that zone to satisfy a

26 constraint; and

27   (b) in each of said multiple data storage devices, assigning one of said

28 frequencies to each head per zone, based on capability of that head and said

29 allocation of the heads.

30

1   24.   The method of claim 23, wherein step (b) further includes the steps

2   of, for each of said multiple data storage devices:

3   (i)   obtaining record/playback performance of each head at a

4   performance metric per zone at one of said read/write frequencies;

5   (ii)   for each zone, ranking the heads from best to worst

6   according to the performance metric; and

7   (iii)   assigning said allocated number of heads, according to the

8   ranking, to one of said read/write frequencies.

9

10 25.   The method of claim 24, further comprising the steps of:

11   repeating steps (i)-(iii) for the remaining heads at the other

12 read/write frequencies.

13

14 26.   The method of claim 24, wherein steps (i)-(iii) are repeated for each

15 of said frequencies, starting from the highest frequency to the lowest frequency.

16

17 27.   The method of claim 24, wherein: step (ii) further includes the steps

18 of selecting said performance metric for the heads in that data storage device for

19 each zone.

20

21 28.   The method of claim 23, wherein for each head in said multiple

22 data storage devices, said number of zones are on different storage media in

23 each data storage device.

24

25 29.   The method of claim 23, wherein for each head in said multiple

26 data storage devices, said number of zones are on the same storage media in

27 each data storage device.

28

29 30.   The method of claim 23, wherein in step (a)(2) said specified

30 criteria comprises providing a specified data storage capacity for each of the

31 multiple data storage devices while maximizing a data storage device yield.

1

2   31.   The method of claim 23, wherein in step (a)(2) said specified

3   criteria comprises maximizing the data storage capacity for each of the multiple

4   data storage devices while providing a specified data storage device yield.

5

6   32.   The method of claim 23, wherein step (b) further includes the steps

7   of calibrating each data storage device for each frequency.

8

9   33.   A method of defining a storage format in multiple data storage

10 devices, each data storage device having a plurality of storage media and a

11 plurality of corresponding data transducer heads, each transducer head for

12 recording on and playback of information from a corresponding storage medium

13 in multiple zones, the method comprising the steps of:

14   (a)   (1) for a sample number of data storage devices, measuring

15 a performance of each head in the sample number of data storage devices at

16 one or more read/write frequencies per zone, and

17   (2) for said multiple data storage devices, based on said

18 performance measurements, jointly: selecting a group of read/write frequencies,

19 two or more read/write frequencies for each zone, and allocating one or more of

20 the heads in each of the multiple data storage devices to each frequency in said

21 group of frequencies per zone; and

22   (b)   in each of said multiple data storage devices, assigning one

23 of said frequencies to each head per zone, based on capability of that head;

24   wherein in each of said multiple data storage devices:

25   said multiple zones on each storage media are arranged as

26 concentric zones, each zone having an inner and an outer boundary at different

27 radial locations on the storage media,

28   such that each storage media includes the same number of

29 concentric zones as other storage media in that data storage device, such that

30 the boundaries of radially similarly situated zones on all the storage media in that

31 data storage device are at the same radial locations.

1

34.   The method of claim 33, wherein radially similarly situated zones on all the storage media include the same number of concentric tracks.

35.   The method of claim 33, wherein at least a number of radially similarly situated zones on all the storage media include different number of concentric tracks.

36.   A method of defining a storage format in multiple data storage devices, each data storage device having a plurality of storage media and a plurality of corresponding data transducer heads, each transducer head for recording on and playback of information from a corresponding storage medium in multiple zones, the method comprising the steps of:

(a)   (1) for a sample number of data storage devices, measuring a performance of each head in the sample number of data storage devices at one or more read/write frequencies per zone, and

(2) for said multiple data storage devices, based on said performance measurements, jointly: selecting a group of read/write frequencies, two or more read/write frequencies for each zone, and allocating one or more of the heads in each of the multiple data storage devices to each frequency in said group of frequencies per zone; and

(b)   in each of said multiple data storage devices, assigning one of said frequencies to each head per zone, based on capability of that head;

wherein in each of said multiple data storage devices:

said multiple zones on each storage media are arranged as concentric zones, each zone having an inner and an outer boundary at different radial locations on the storage media,

such that each storage media includes a sequence of concentric zones, such that the boundaries of at least a number sequentially similarly situated zones on different storage media in that data storage device are at different radial locations.

1

2   37.   The method of claim 36, wherein sequentially similarly situated

3   zones on all the storage media include the same number of concentric tracks.

4

5   38.   The method of claim 36, wherein at least a number of sequentially

6   similarly situated zones on all the storage media include different number of

7   concentric tracks.

8

9   39.   A data storage device comprising a plurality of pairs of storage

10   media surfaces and transducer heads, each transducer head for recording on

11   and playback of information from a corresponding storage medium in multiple

12   zones, and a controller that controls the heads for reading and writing data on the

13   media surfaces, the controller being programmed to write data in a storage

14   format defined by the steps including:

15   (a)   (1) for a sample number of data storage devices, measuring a

16   performance of each head in the sample number of data storage devices at one

17   or more read/write frequencies per zone, and

18   (2) for said data storage device, based on said performance

19   measurements, jointly: selecting a group of read/write frequencies, two or more

20   read/write frequencies for each zone, and allocating one or more of the heads in

21   that data storage devices to each frequency in said group of frequencies per

22   zone; and

23   (b)   in said data storage device, assigning one of said frequencies to

24   each head per zone, based on capability of that head, thereby defining said

25   storage format.

26

27   40.   The data storage device of claim 39, wherein in step (a)(1)

28   measuring performance of each head further includes the steps of measuring a

29   record/playback performance of that head according to a performance metric at

30   different frequencies.

31

1   41.   The data storage device of claim 39, wherein step (a) is performed

2 in a storage device design phase and step (b) is performed in a storage device

3 manufacturing phase.

4

5   42.   The data storage device of claim 39, wherein step (a)(1) further

6 includes the steps of calibrating each of said multiple data storage devices for

7 each said frequencies.

8

9   43.   The data storage device of claim 39, wherein step (a)(2) further

10 includes the steps of jointly selecting said frequencies and allocating said heads

11 to said frequencies, to satisfy a specified constraint.

12

13   44.   The data storage device of claim 43, wherein:

14   step (a)(1) further includes the steps of, for each of said sample

15 number of data storage devices:

16   selecting a performance metric for the heads in that data

17 storage device for each zone; and

18   measuring performance of each head at different

19 frequencies per zone based on said metric;

20   step (a)(2) further includes the steps of, for the multiple data

21 storage devices:

22   based on said performance measurements, for each zone

23 allocating an integral number of heads to each of said frequencies for that zone

24 to satisfy the specified constraint.

25   /

26   45.   The data storage device of claim 44, wherein in step (a)(2)

27 allocating said heads to said frequencies per zone further includes the steps of:

28 for each zone, based on the performance of the heads in a plurality of zones,

29 allocating an integral number of heads to each of said frequencies for that zone

30 to satisfy said constraint for said multiple data storage devices.

31

1   46.   The data storage device of claim 44, wherein step (a)(2) further

2   includes the steps of:

3   based on said performance measurements, generating

4   record/playback frequency capability distributions of the heads in the sample

5   number of disk drives, at each zone for a target performance metric, and

6   based on said distributions, allocating an integral number of heads

7   to each of said frequencies for that zone to satisfy said constraint for the said

8   multiple data storage devices.

9

10   47.   The data storage device of claim 44, wherein said constraint

11   comprises providing a required data storage capacity for each of said multiple

12   data storage devices.

13

14   48.   The data storage device of claim 43, said constraint comprises

15   providing a required data storage device yield for said multiple data storage

16   devices.

17

18   49.   The data storage device of claim 43, wherein said constraint

19   comprises maximizing the data storage device yield while providing a specified

20   data storage device capacity of the multiple data storage devices.

21

22   50.   The data storage device of claim 43, wherein said constraint

23   comprises maximizing the data storage capacity for each of the multiple data

24   storage devices while providing a specified data storage device yield.

25

26   51.   A data storage device comprising a plurality of pairs of storage

27   media surfaces and transducer heads, each transducer head for recording on

28   and playback of information from a corresponding storage medium in multiple

29   zones, and a controller that controls the heads for reading and writing data on the

30   media surfaces, the controller being programmed to write data in a storage

31   format defined by the steps including:

1   (a)   (1) for a sample number of data storage devices, measuring a

2   performance of each head in the sample number of data storage devices at one

3   or more read/write frequencies per zone, and based on said performance

4   measurements, generating performance distributions of the heads in said sample

5   number of data storage devices, at each zone for a target performance metric,

6   and

7   (2) for the data storage device, based on said performance

8   distributions, jointly: selecting a group of read/write frequencies, two or more

9   read/write frequencies for each zone, and allocating one or more of the heads in

10   each of the multiple data storage devices to each frequency in said group of

11   frequencies per zone; and

12   (b)   in the data storage devices, assigning one of said frequencies to

13   each head per zone, based on capability of that head.

14

15   52.   The data storage device of claim 51, wherein generating said

16   distributions further includes the steps of:

17   estimating record/playback frequency capability of each head

18   based on said measurements, and

19   generating record/playback frequency capability distributions of the

20   heads at each zone for a target performance metric based on said estimated

21   record/playback frequency capabilities the heads.

22

23   53.   The data storage device of claim 51 wherein the steps of

24   generating said distributions is performed in a post-processing phase.

25

26   54.   The data storage device of claim 51, wherein generating said

27   distributions includes the steps of: generating record/playback frequency

28   capability distributions of the heads based on said performance measurements at

29   a target performance metric for the heads in said sample number of data storage

30   devices.

31

55.   The data storage device of claim 51, wherein in step (a)(2) selecting said group of frequencies further includes the steps of selecting said group of frequencies to satisfy a specified constraint.

56.   A data storage device comprising a plurality of pairs of storage media surfaces and transducer heads, each transducer head for recording on and playback of information from a corresponding storage medium in multiple zones, and a controller that controls the heads for reading and writing data on the media surfaces, the controller being programmed to write data in a storage format defined by the steps including:

(a)   (1) for a sample number of data storage devices, measuring a performance of each head in the sample number of data storage devices at one or more read/write frequencies per zone, and

(2) for said data storage device, based on said performance measurements, jointly: selecting a group of read/write frequencies, two or more read/write frequencies for each zone, and for each zone allocating an integral number of heads to each of said frequencies for that zone to satisfy a constraint; and

(b)   in said data storage device, assigning one of said frequencies to each head per zone, based on capability of that head and said allocation of the heads.

57.   The data storage device of claim 56, wherein step (b) further includes the steps of, for the data storage device:

(i)   obtaining record/playback performance of each head at a performance metric per zone at one of said read/write frequencies;

(ii)   for each zone, ranking the heads from best to worst according to the performance metric; and

(iii)   assigning said allocated number of heads, according to the ranking, to one of said read/write frequencies.

1   58.   The data storage device of claim 57, wherein step (b) further

2 comprises the steps of:

3   repeating steps (i)-(iii) for the remaining heads at the other

4 read/write frequencies.

5

6   59.   The data storage device of claim 57, wherein step (b) further

7 includes the steps of selecting said performance metric for the heads in that data

8 storage device for each zone.

9

10   60.   The data storage device of claim 56, wherein in step (a)(2) said

11 specified criteria comprises providing a specified data storage capacity for the

12 data storage devices while maximizing a data storage device yield.

13

14   61.   The data storage device of claim 56, wherein in step (a)(2) said

15 specified criteria comprises maximizing the data storage capacity for each of the

16 multiple data storage devices while providing a specified data storage device

17 yield.

18

19   62.   A data storage device comprising a plurality of pairs of storage

20 media surfaces and transducer heads, each transducer head for recording on

21 and playback of information from a corresponding storage medium in multiple

22 zones, and a controller that controls the heads for reading and writing data on the

23 media surfaces, the controller being programmed to write data in said multiple

24 zones, wherein:

25   said multiple zones on each storage media are arranged as

26 concentric zones, each zone having an inner and an outer boundary at different

27 radial locations on the storage media,

28   such that each storage media includes the same number of

29 concentric zones as other storage media in that data storage device, wherein the

30 boundaries of radially similarly situated zones on all the storage media in that

31 data storage device are at the same radial locations.

63. The data storage device of claim 62, wherein radially similarly situated zones on all the storage media include the same number of concentric tracks.

64. The data storage device of claim 62, wherein at least a number of radially similarly situated zones on all the storage media include different number of concentric tracks.

65. A data storage device comprising a plurality of pairs of storage media surfaces and transducer heads, each transducer head for recording on and playback of information from a corresponding storage medium in multiple zones, and a controller that controls the heads for reading and writing data on the media surfaces, the controller being programmed to write data in said multiple zones, wherein:

said multiple zones on each storage media are arranged as concentric zones, each zone having an inner and an outer boundary at different radial locations on the storage media,

such that each storage media includes a sequence of concentric zones, such that the boundaries of at least a number sequentially similarly situated zones on different storage media in that data storage device are at different radial locations.

66. The data storage device of claim 65, wherein sequentially similarly situated zones on all the storage media include the same number of concentric tracks.

67. The data storage device of claim 65, wherein at least a number of sequentially similarly situated zones on all the storage media include different number of concentric tracks.